



Pin-out diagram

| From Pin# | To Pin# |
|--------------|-------------|
| J1 10 Yellow | J2 2 Yellow |
| J1 9 Green | J2 1 Green |
| J1 12 Red | J3 4 Red |
| J1 16 Purple | J4 1 Purple |
| J1 15 Black | J4 2 Black |

Electrical Properties:
 1. It should be no any open/short, Miswiring and intermittent failures.
 2. The cable shall be 100% electrical test.

| No | Material | Description | Qty |
|----|----------|------------------------------|------|
| 1 | Wire | UL 1007 24AWG (Xiene) | 5Pcs |
| 2 | Terminal | A2211T (Shengyi) | 5Pcs |
| 3 | Housing | A2211H-2*9P (Shengyi) | 1Pc |
| 4 | Terminal | TJC82.54 T(1/2 Gold) (Jinda) | 4Pcs |
| 5 | Housing | TJC82.54-1P (Jinda) | 4Pcs |
| 6 | Terminal | 8611 (E.C.I) | 1Pc |
| 7 | Housing | 5.08-4P Female (Jinda) | 1Pc |



| REV | DATE | REVISE CONTENT | PAGE | REV | 1:1 | P/N | DWG NO | DWG | APP | Lee | DATE |
|-----|------------|----------------|------|-----|-----|-----|--------|-----|-----|------|------------|
| 1 | 2011/11/29 | | 1 | 1 | 1 | | | | CHK | J.Ke | 2011/11/29 |
| | | | | | | | | | APP | Lee | 2011/11/29 |

1: UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN UNITS TOLERANCE ARE AS DWG

2: ALL DIMENSIONS ARE "mm"