

**Neotec Semiconductor Ltd.**

新德科技股份有限公司

**NT7065B****40-Channel Segment / Common  
Driver For Dot Matrix LCD****Introduction**

The NT7065B is a LCD driver IC which is fabricated by low power CMOS technology. Basically this IC consists of 20 x 2 bit bi-directional shift register, 20 x 2 bit data latch and 20 x 2 bit driver. This IC can be used as common or segment driver.

**Function**


- Dot matrix LCD driver with 40 channel output.
- Selects function to use common/segment drivers simultaneously.
- Input / Output signal.
  - Output: 20 x 2 channel waveform for LCD driving
  - Input: Serial display date and control signal from the controller LSI.
  - Bias voltage (V1-V6)

**Features**

- Display driving bias: static~1/5
- Power supply voltage: 2.7~5.5V
- Supply voltage for display: 3~10V ( $V_{LCD}=V_{DD}-V_{EE}$ )
- Interface: (Controller NT7066U, NT7070B, NT7076U)
- CMOS Process
- Bare chip available

**Neotec Semiconductor Ltd.**

新德科技股份有限公司

**NT7065B****Block Diagram**

**Neotec Semiconductor Ltd.**

新德科技股份有限公司

**NT7065B****Pin Description**

PIN	INPUT/OUTPUT	NAME	DESCRIPTION	INTERFACE																									
V <sub>DD</sub>	Power	Operating Voltage	For logical circuit (2.7~5.5V)	Power Supply																									
GND			0V(GND)																										
V <sub>EE</sub>		Negative Supply Voltage	For LCD driver circuit																										
V1,V2	Input	Bias Voltage	Bias voltage level for LCD driver (select level)	Power																									
SC1~SC20	Output	LCD Driver	LCD driver output	LCD																									
V3,V4	Input	Bias Voltage	Bias voltage level for LCD drive (non-select level)	Power																									
SHL1	Input	Part1 Data Interface	Selection of the shift direction of part1 shift register <table border="1"><tr><td>SHL1</td><td>DL1</td><td>DR1</td></tr><tr><td>V<sub>DD</sub></td><td>out</td><td>in</td></tr><tr><td>GND</td><td>in</td><td>out</td></tr></table>	SHL1	DL1	DR1	V <sub>DD</sub>	out	in	GND	in	out	V <sub>DD</sub> or GND																
SHL1	DL1	DR1																											
V <sub>DD</sub>	out	in																											
GND	in	out																											
DL1,DR1	Input/Output	Data input/output of part1 shift register																											
SC21~SC40	Output	LCD Driver	LCD driver output																										
V5,V6	Input	Bias Voltage	Bias voltage level for LCD drive (non-select level)	Power																									
SHL2	Input	Part2 Data Interface	Selection of the shift direction of part2 shift register <table border="1"><tr><td>SHL2</td><td>DL2</td><td>DR2</td></tr><tr><td>V<sub>DD</sub></td><td>out</td><td>in</td></tr><tr><td>GND</td><td>in</td><td>out</td></tr></table>	SHL2	DL2	DR2	V <sub>DD</sub>	out	in	GND	in	out	V <sub>DD</sub> or GND																
SHL2	DL2	DR2																											
V <sub>DD</sub>	out	in																											
GND	in	out																											
DL2,DL2	Input/Output	Data input/output of part2 shift register																											
M	Input	Alternated signal for LCD drive output	<table border="1"> <tr> <th>PART</th> <th>FCS</th> <th>CL1</th> <th>CL2</th> <th>M polarity</th> </tr> <tr> <td>1</td> <td>GND</td> <td>Latch clock </td> <td>Shift clock </td> <td>M</td> </tr> <tr> <td></td> <td>V<sub>DD</sub></td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>GND</td> <td>Latch clock </td> <td>Shift clock </td> <td>— M</td> </tr> <tr> <td></td> <td>V<sub>DD</sub></td> <td></td> <td></td> <td></td> </tr> </table>		PART	FCS	CL1	CL2	M polarity	1	GND	Latch clock 	Shift clock 	M		V <sub>DD</sub>				2	GND	Latch clock 	Shift clock 	— M		V <sub>DD</sub>			
PART	FCS	CL1	CL2	M polarity																									
1	GND	Latch clock 	Shift clock 	M																									
	V <sub>DD</sub>																												
2	GND	Latch clock 	Shift clock 	— M																									
	V <sub>DD</sub>																												
CL1,CL2	Input	Data shift/latch clock																											
FCS	Input	Mode selection	Shift/latch clock of display data and polarity of M signal are changed by FCS signal. By setting FCS to V <sub>DD</sub> level, user can select the function that use part1 as segment driver and part2 as common driver simultaneously.	Controller																									

**Neotec Semiconductor Ltd.**

新德科技股份有限公司

**NT7065B****Maximum Absolute Limit (Ta=25°C)**

Characteristic	Symbol	Value	Unit
Power supply voltage	V <sub>DD</sub>	-0.3~+7.0	V
Driver supply voltage	V <sub>LCD</sub>	V <sub>DD</sub> -10.5~V <sub>DD</sub> +0.3	V
Input voltage 1	V <sub>IN1</sub>	-0.3~V <sub>DD</sub> +0.3	V
Input voltage 2 (V1~V6)	V <sub>IN2</sub>	V <sub>DD</sub> +0.3~V <sub>EE</sub> -0.3	V
Operating temperature	T <sub>opr</sub>	-30~+85	°C
Storage temperature	T <sub>tsg</sub>	-55~+125	°C

- Voltage grater than above may damage to the circuit
- VEE connect a protection resistor (220Ω±5%)

**Electrical Characteristics**DC characteristics (V<sub>DD</sub>=2.7~5.5V, V<sub>DD</sub>-V<sub>EE</sub>=3~10V, Ta=+25°C)

Characteristic	Symbol	Test condition	Min	Max	Unit	Applicable pin
Operating current*	I <sub>DD</sub>	f <sub>CL2</sub> =400KHz	-	1	mA	-
Supply current*	I <sub>EE</sub>	f <sub>CL1</sub> =1KHz	-	10	μA	-
Input high voltage	V <sub>IH</sub>	-	0.7V <sub>DD</sub>	V <sub>DD</sub>	V	CL1,CL2,DL1, DL2,DR1,DR2, SHL1,SHL2,M, FCS
Input low voltage	V <sub>IL</sub>		0	0.3V <sub>DD</sub>		
Input leakage current	I <sub>LKG</sub>	V <sub>IN</sub> =0~VDD	-5	5	μA	-
Output high voltage	V <sub>OH</sub>	I <sub>OH</sub> =-0.4mA	V <sub>DD</sub> -0.4	-	V	DL1,DL2,DR1, DR2
Output low voltage	V <sub>OL</sub>	I <sub>OL</sub> =+0.4mA	-	0.4		
Voltage descending	V <sub>D1</sub>	I <sub>ON</sub> =0.1mA for one of SC1~SC40	-	1.1		V(V1~V6)-SC( SC1~SC40)
	V <sub>D2</sub>	I <sub>ON</sub> =0.05mA for one of SC1~SC40	-	1.5		
Leakage current	I <sub>V</sub>	V <sub>IN</sub> =V <sub>DD</sub> ~V <sub>EE</sub> (output SC1~SC40 : floating)	-10	10	μA	V1~V6

\*Input/Output current is excluded; When input at the intermediate level with CMOS, excessive current flows through the input circuit to the power supply. To avoid this, input level must be fixed at "H" or "L".

# Neotec Semiconductor Ltd.

新德科技股份有限公司




# NT7065B

## AC characteristics ( $V_{DD}=2.7\sim 5.5V$ , $V_{DD}-V_{EE}=3\sim 10V$ , $T_a=+25^\circ C$ )

Characteristic	Symbol	Test condition	Min	Max	Unit	Applicable pin
Data shift frequency	$f_{CL}$	-	-	400	KHz	CL2
Clock high level width	$t_{WCKH}$	-	800	-	nS	CL1, CL2
Clock low level width	$t_{WCKL}$	-	800	-		CL2
Clock set-up time	$t_{SL}$	From CL2 to CL1	500	-		CL1, CL2
	$t_{LS}$	From CL1 to CL2	500	-		
Clock rise/fall time	$t_R/t_F$	-	-	200		DL1,DL2,DR1, DR2,FLM
Data set-up time	$t_{SU}$	-	300	-		
Data hold time	$t_{DH}$	-	300	-		
Data delay time	$t_D$	CL=15pF	-	500		DL1,DL2,DR1, DR2

## Timing Characteristics



# Neotec Semiconductor Ltd.

新德科技股份有限公司




NT7065B

## Functional Description


### 1) To drive segment type

When the FCS is connected to GND, NT7065B (SC1~SC40) is operated as segment driver.




### 2) To drive common type

When the FCS is connected to V<sub>DD</sub>, only part2 (SC21~SC40) of NT7065S is operated as common driver.



**Neotec Semiconductor Ltd.**



新德科技股份有限公司

**NT7065B****LCD Output Waveforms**

\*1: To use for same function of part1 and part2, V3 and V5, V4 and V6 of power supply for LCD driver are short circuited respectively.


**Neotec Semiconductor Ltd.**

新德科技股份有限公司

**NT7065B****Application circuit****1) Segment driver****2) Common driver**


**Neotec Semiconductor Ltd.**

新德科技股份有限公司

**NT7065B****3) Segment/Common driver**

**Neotec Semiconductor Ltd.**

新德科技股份有限公司

**NT7065B****Pad Diagram****Note:** Please connects the substrate to V<sub>DD</sub> or floating

**Neotec Semiconductor Ltd.**

新德科技股份有限公司

**NT7065B****Pad Location****Note:** (0,0) is center in the chip

Pad		Coordinates		Pad		Coordinates	
NO.	Name	X	Y	NO.	Name	X	Y
1	VEE	-1120.20	-642.50	31	SC28	1117.50	865.20
2	CL1	-1062.50	-865.20	32	SC27	992.50	865.20
3	CL2	-937.50	-865.20	33	SC26	867.50	865.20
4	GND	-812.50	-865.20	34	SC25	742.50	865.20
5	DL1	-687.50	-865.20	35	SC24	617.50	865.20
6	DR1	-562.50	-865.20	36	SC23	492.50	865.20
7	DL2	-437.50	-865.20	37	SC22	367.50	865.20
8	DR2	-312.50	-865.20	38	SC21	242.50	865.20
9	M	-187.50	-865.20	39	SC20	117.50	865.20
10	SHL1	-62.50	-865.20	40	SC19	-7.50	865.20
11	SHL2	62.50	-865.20	41	SC18	-132.50	865.20
12	FCS	187.50	-865.20	42	SC17	-257.50	865.20
13	V1	332.50	-865.20	43	SC16	-382.50	865.20
14	V2	457.50	-865.20	44	SC15	-507.50	865.20
15	V3	582.50	-865.20	45	SC14	-632.50	865.20
16	V4	707.50	-865.20	46	SC13	-757.50	865.20
17	V5	832.50	-865.20	47	SC12	-882.50	865.20
18	V6	957.50	-865.20	48	SC9	-1120.20	857.20
19	SC40	1082.50	-865.20	49	SC10	-1120.20	732.50
20	SC39	1120.20	-627.50	50	SC11	-1120.20	607.50
21	SC38	1120.20	-502.50	51	SC8	-1120.20	482.50
22	SC37	1120.20	-377.50	52	SC7	-1120.20	357.50
23	SC36	1120.20	-252.50	53	VDD	-1120.20	232.50
24	SC35	1120.20	-127.50	54	SC6	-1120.20	107.50
25	SC30	1120.20	-2.50	55	SC5	-1120.20	-17.50
26	SC31	1120.20	122.50	56	SC4	-1120.20	-142.50
27	SC32	1120.20	247.50	57	SC3	-1120.20	-267.50
28	SC33	1120.20	372.50	58	SC2	-1120.20	-392.50
29	SC34	1120.20	479.50	59	SC1	-1120.20	-517.50
30	SC29	1120.20	622.50				